

FOIL TAPES

flash this code
for technical support
of this product



SPECIFICATIONS

100 X 25

| | |
|-------------------------|---------------------|
| Application temperature | 18 °C to 50 °C |
| Substrate type | polypropylene film |
| Support thickness | 32 microns |
| Tensile strength | 4,5 kg / cm |
| Elongation at break | 140 % |
| Solvent | no |
| Width | 100 mm |
| Length | 25 m |
| Packing | 18 rolls per carton |
| Cardboard core | 78 mm |

COMPOSITION

Metallised polypropylene ribbon coated with an acrylic adhesive.

USAGE

- For use on a metallised support. (For aluminium material, use the adher'alu tape).
- To stick perfectly over time, the surface must be dry and clean.
- Respect the application temperatures at the time of installation.

Recommendation : must be stored in a cool, dry place away from direct sources of heat.

flash this code
for technical support
of this product



SPECIFICATIONS

ADHER'ALU

| | |
|-----------------------------|--|
| Application temperature | 5 °C to 60 °C |
| Substrate type | aluminium |
| Support thickness | 40 microns |
| Protective | by siliconised paper 60 g / m ² |
| Type of adhesive | acrylic |
| Total thickness of the tape | 130 µm |
| Adhesion on steel | 6 N / cm |
| Elongation at break | 9 % |
| Temperature | -20 °C to 120 °C |
| Fire rated | M1 or UI723 |
| Width | 75 mm |
| Length | 50 m |
| Packing | 16 rolls per carton |
| Cardboard core | 76 mm |

COMPOSITION

Aluminium tape with an acrylic adhesive protected by a silicon spacer.

USAGE

- For use on a aluminium support. (For metallised support use 100x25 XL MAT tape).
- To stick perfectly over time, the surface must be dry and clean.
- Respect the application temperatures at the time of installation.
- The adhesive should be stored flat and away from damp.