

flash this code
for technical support
of this product



SPECIFICATIONS

Dimensions	1,54 m x 19,6 ml
Surface area	30 m ²
Weight (roll)	+ / - 9,3 kg
Vapour permeability (Sd)	0,072 m
Weight (m ²)	+ / - 310 g
Thickness	+ / - 4 mm
Thermal conductivity (λ) <small>European standard EN12667</small>	0,028 W / (m.K)
Mechanical resistance	R2
Maximum tensile force L x T (N/50 mm)	+ / - 360 x 230
Elongation at break L x T (%)	+ / - 11 x 7
Resistance to nail tearing L x T (n)	+ / - 245 x 305
Resistance to penetration of the water	W1
Resistance to air permeation	0,5 m ³ / (m ² .h.50Pa)
After aging	
Maximum tensile force L x T (N/50 mm)	+ / - 440 x 730
Elongation at break (%)	5 x 7
Resistance to penetration of the water	W1

COMPOSITION

5 COMPONENTS

- 2 130 g/m² reinforced metallised polyester films
- 2 polyester waddings - 250 g / m²
- 1 waterproof breathable membrane

USAGE

- Store your rolls away from the rain and sun.
- For optimal installation, use a **XL MAT** tape.
- It must not be placed near a direct source of heat such as a fireplace, a sleeve or around a valve or boiler pipes, etc... For these applications, use **A1** rated insulation material.

QUICK AND EASY INSTALLATION



MEASURE



CUT



STAPLE



ASSEMBLE

100 x 25 compatible tape

15 M² ROLL